

One-Light Wall Sconce

Wall mounted • Damp location listed



Description:

Inspired by beautiful glass forms commonly found in a science lab, Beaker has a heightened sense of modern industrial styling. The 9W LED source offers energy efficient and cost savings benefits, while the industrial-inspired design complements a variety of mid-century modern interior designs. The one-light wall sconce has champagne glass with an Antique Bronze frame.

Specifications:

- Antique Bronze (-20) (painted)
- Steel Construction
- Champagne glass round
- Inspired by beautiful glass forms commonly found in a science lab.
- Heightened sense of modern industrial styling.
- Vessels are suspended from herringbone cloth cords.
- 623 lumens 69.2 lumens/watt per module (source)
- 3000K color temperature, 90+ CRI.
- Dimmable to 10% brightness (See Dimming Notes)
- Back plate covers a standard 4" octagonal recessed outlet box
- Mounting strap for outlet box included
- 36" of wire supplied
- ENERGY STAR® qualified

Performance:

Number of Modules	1
Input Power	9w
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW (Source)	623/69.2 (LM-82)
Lumens/LPW (Delivered)	252/35 (LM-79)
CCT	3000 K
CRI	90+
Life (hours)	60,000 (L70/TM-21)
FCC	Meets FCC Title 47, Part 15 Class B
Min. Start Temp	-30 °C
Max. Operating Temp	30 °C
Warranty	5 year warranty
Labels	cCSAus Damp location listed ENERGY STAR® qualified

P7125-2030K9

Images:



Dimensions:

Width: 10-1/4"
Depth: 11-7/8"
Height: 16-5/8"
H/CTR: 4"

Photometrics:

P7125-2030K9

ELECTRICAL DATA	P7125-2030K9
Input Voltage	120 V
Input Frequency	60 Hz
Input Current	0.075 A
Input Power	9
Power Factor	Greater than 0.90
THD	<20%
FCC	Meets FCC Title 47, Part 15 Class B
Operating Temperature	-30 °C to 30 °C
Dimming	Yes*

*See Dimming Notes for more information

P7125-2030K9


LED Light Engine: 3000 K 90+
 System Wattage: 9
 Fixture delivered lumens: 252
 Fixture Efficacy: 35
 Spacing Criteria: 1.1

CANDELA DISTRIBUTION

DEG	CANDELA	LUMENS
0	158	
5	154	15
15	134	38
25	117	54
35	107	65
45	49	38
55	14	14
65	12	12
75	8	8
85	4	4
90	2	
95	1	1
105	1	1
115	1	1
125	1	1
135	0	0
145	0	0
155	0	0
165	0	0
175	0	0
180	0	

ZONAL LUMEN SUMMARY

ZONE	LUMENS	%FIXT
0-30	106	42.2
0-40	171	67.9
0-60	224	88.6
0-90	248	98.4
90-120	4	1.4
90-130	4	1.6
90-150	4	1.6
90-180	4	1.6
0-180	252	100.0



Test **16.00187** Test Date **1/25/16**

P7125-2030K9**Dimming Notes:**

P7125 is designed to be compatible with many ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls

Lutron Nova T NTELV-300

Lutron Vieri VTELV-600

Lutron Ariadni AYCL-153P

Lutron Diva DVCL-153P

Lutron Maestro MAELV-600

Lutron spacer/system SPSELV-600

Leviton Renoir II AWRMG-EAW

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.